

Product data sheet

Specifications



LED bulb, Harmony XVB, BA 15d, yellow, steady light, 24V AC/DC

DL1BDB8

⚠ To be discontinued on: Dec 31, 2025

⚠ To be discontinued

Main

Range compatibility	Harmony XVP Harmony XVB Harmony XVD
Accessory / separate part designation	Protected LED bulb
Accessory / separate part type	LED bulb
Accessory / separate part category	Lighting accessories
Accessory / separate part destination	Beacon and indicator bank
[Us] rated supply voltage	24 V AC/DC
Signalling type	Steady
Signalling colour	Yellow
Sale per indivisible quantity	1

Complementary

Current consumption	47 mA
Bulb base	BA 15d
Net weight	0.015 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.700 cm
Package 1 Width	4.500 cm
Package 1 Length	3.500 cm
Package 1 Weight	11.000 g
Unit Type of Package 2	S01
Number of Units in Package 2	60
Package 2 Height	15.000 cm
Package 2 Width	15.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.042 kg

Contractual warranty

Warranty

18 months



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	34
---	----

Use Better

Materials and Substances

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
-----------------------------------	--

REACH Regulation	REACH Declaration
------------------	-----------------------------------

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
---------------------------	--

Use Again

Repack and remanufacture

Circularity Profile	No need of specific recycling operations
---------------------	--

WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

Take-back	No
-----------	----

Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony XVB

Robust product performance with high IP protection and IK05 shock resistance



Conformity with International standards



Greater loudness up to 90dB with continuous and intermittent tones



Beacon lens on top with high intensity 5J, 10J Xenon flash, increase visibility from top and surrounding



Offer Marketing Illustration

Product benefits / Features



The infographic features a central image of two Harmony XVB light fixtures: one with five stacked lens units in red, yellow, green, blue, and red, and another with a single red lens unit. The background is a vibrant green. The title 'Features Harmony XVB' is at the top center. Five circular icons with white backgrounds and green symbols are arranged around the central image, each with a corresponding text block. The icons represent: a lightbulb (light source), a lightbulb with a lightning bolt (maintenance-free), a wrench and screwdriver (connector), a checkmark (protection), and a leaf (flexibility).

Features Harmony XVB

- 3 types of light source:** 10-Watt incandescent bulb, built-in high-efficiency LEDs, 5 and 10-joule discharge tube
- 100,000 hours of maintenance-free lighting** thanks to "LED Protected" technology
- Connector with removable base, axial, or side cable entry, immediate assembly, and fixing using a locking ring**
- High degree of protection (IP66) and Shock resistance (IK05)**
- Fully flexible and interchangeable construction of up to 5 lens units (six colors of light lens unit)**