

# Product data sheet

Specifications



## Pragma flush enclosure - IP40 - 3 x 13 modules - without door

PRA25313

⚠ Discontinued on: Oct 31, 2023

⚠ Discontinued

### Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Width	Wall: 366 mm Outside: 396 mm
Height	Wall: 630 mm Outside: 660 mm
Depth	Wall : 86 mm Outside : 21 mm
Nb of 18 mm modules per row	13
Nb of horizontal rows	3
Electrical insulation class	Class II Double insulation
Provided equipment	2 x terminal block 1 x identification label 1 x marking kit 1 x blanking plate strip
Type of door	Without

### Complementary

Enclosure mounting	Flush
9 mm pitches	26
Total number of 18 mm modules	39
Power dissipation in W	56 W
[In] rated current	90 A
[Ui] rated insulation voltage	400 V
Type of rail	DIN
Mounting plate description	Without mounting plate
cable entry	Side pre-cutouts Cable or tube Removable plates
Number of terminal blocks	1 earth (Quick) with 24 outgoers 1 neutral (Quick) with 24 outgoers
Distribution block outgoers	3 x 25 mm <sup>2</sup> for earth 21 x 4 mm <sup>2</sup> for earth 3 x 25 mm <sup>2</sup> for neutral 21 x 4 mm <sup>2</sup> for neutral

<b>Enclosure material</b>	Back part: technoplastic Front face: technoplastic
<b>Colour</b>	Enclosure: white (RAL 9016) Front face: grey (RAL 7004)
<b>Targeted country</b>	Hungary Russia Greece Czech republic
<b>Embedding depth</b>	86 mm
<b>Internal depth</b>	84 mm

## Environment

<b>Fire resistance</b>	Back part: 650 °C Front face: 650 °C
<b>IP degree of protection</b>	IP30 without door IP40 with door
<b>IK degree of protection</b>	IK08 without door IK09 with door
<b>Overvoltage category</b>	II
<b>Ambient air temperature for operation</b>	-25...60 °C
<b>Standards</b>	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	12.0 cm
<b>Package 1 Width</b>	41.5 cm
<b>Package 1 Length</b>	66.5 cm
<b>Package 1 Weight</b>	4.431 kg
<b>Unit Type of Package 2</b>	P12
<b>Number of Units in Package 2</b>	21
<b>Package 2 Height</b>	120.0 cm
<b>Package 2 Width</b>	80.0 cm
<b>Package 2 Length</b>	120.0 cm
<b>Package 2 Weight</b>	105.051 kg

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **25**

Environmental Disclosure [Product Environmental Profile](#)

### Use Better

#### Materials and Substances

[EU RoHS Directive](#)

Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation

[REACH Declaration](#)

### Use Again

#### Repack and remanufacture

Circularity Profile

No need of specific recycling operations

Halogen content performance

Halogen free product